

# Appendix B: FEMA Flood Insurance Rate Maps

Technical Memorandum #1 | Inventory and Analysis of Existing Conditions December 2019

This map is for use in administering the National Flood Insurance Program. It does not necessarily identify all areas subject to flooding, particularly from local drainage sources of small size. The **community map repository** should be consulted for possible updated or additional flood hazard information.

To obtain more detailed information in areas where **Base Flood Elevations** (BFEs) and/or **floodways** have been determined, users are encouraged to consult the Flood Profiles and Floodway Data and/or Summary of Stillwater Elevations tables contained within the Flood Insurance Study (FIS) report that accompanies this FIRM. Users should be aware that BFEs shown on the FIRM represent rounded whole-foot elevations. These BFEs are intended for flood insurance rating purposes only and should not be used as the sole source of flood elevation information. Accordingly, flood elevation data presented in the FIS report should be utilized in conjunction with the FIRM for purposes of construction and/or floodplain management.

Coastal Base Flood Elevations shown on this map apply only landward of 0.0' North American Vertical Datum of 1988 (NAVD 88). Users of this FIRM should be aware that coastal flood elevations are also provided in the Summary of Stillwater Elevations tables in the Flood Insurance Study report for this jurisdiction. Elevations shown in the Summary of Stillwater Elevations tables should be used for construction and/or floodplain management purposes when they are higher than the elevations shown on this FIRM.

Boundaries of the **floodways** were computed at cross sections and interpolated between cross sections. The floodways were based on hydraulic considerations with regard to requirements of the National Flood Insurance Program. Floodway widths and other pertinent floodway data are provided in the Flood Insurance Study report for this jurisdiction.

Certain areas not in Special Flood Hazard Areas may be protected by **flood control structures**. Refer to Section 2.4 "Flood Protection Measures" of the Flood Insurance Study report for information on flood control structures for this jurisdiction.

The **projection** used in the preparation of this map was Universal Transverse Mercator (UTM) zone 18N. The **horizontal datum** was NAD 83, GRS80 spheroid. Differences in datum, spheroid, projection or UTM zones used in the production of FIRMs for adjacent jurisdictions may result in slight positional differences in map features across jurisdiction boundaries. These differences do not affect the accuracy of this FIRM.

Flood elevations on this map are referenced to the North American Vertical Datum of 1988. These flood elevations must be compared to structure and ground elevations referenced to the same **vertical datum**. For information regarding conversion between the National Geodetic Vertical Datum of 1929 and the North American Vertical Datum of 1988, visit the National Geodetic Survey website at <a href="http://www.ngs.noaa.gov">http://www.ngs.noaa.gov</a> or contact the National Geodetic Survey at the following address:

NGS Information Services NOAA, N/NGS12 National Geodetic Survey SSMC-3, #9202 1315 East-West Highway Silver Spring, Maryland 20910-3182 (301) 713-3242

To obtain current elevation, description, and/or location information for **bench marks** shown on this map, please contact the Information Services Branch of the National Geodetic Survey at (301) 713-3242, or visit its website at <a href="http://www.ngs.noaa.gov">http://www.ngs.noaa.gov</a>.

Base map information shown on this FIRM was derived from digital orthophotography provided by the New York State Office of Cyber Security & Critical Infrastructure Coordination. This information was provided as 30-centimeter and 60-centimeter resolution natural color orthoimagery from photography dated April-May 2004


Based on updated topographic information, this map reflects more detailed and up-to-date **stream channel configurations and floodplain delineations** than those shown on the previous FIRM for this jurisdiction. As a result, the Flood Profiles and Floodway Data tables in the Flood Insurance Study Report (which contains authoritative hydraulic data) may reflect stream channel distances that differ from what is shown on this map. Also, the road to floodplain relationships for unrevised streams may differ from what is shown on previous maps.

**Corporate limits** shown on this map are based on the best data available at the time of publication. Because changes due to annexations or de-annexations may have occurred after this map was published, map users should contact appropriate community officials to verify current corporate limit locations.

Please refer to the separately printed **Map Index** for an overview map of the county showing the layout of map panels; community map repository addresses; and a Listing of Communities table containing National Flood Insurance Program dates for each community as well as a listing of the panels on which each community is located.

Contact the **FEMA Map Service Center** at 1-800-358-9616 for information on available products associated with this FIRM. Available products may include previously issued Letters of Map Change, a Flood Insurance Study report, and/or digital versions of this map. The FEMA Map Service Center may also be reached by Fax at 1-800-358-9620 and its website at <a href="http://msc.fema.gov">http://msc.fema.gov</a>.

If you have **questions about this map** or questions concerning the National Flood Insurance Program in general, please call **1-877-FEMA MAP** (1-877-336-2627) or visit the FEMA website at <a href="http://www.fema.gov">http://www.fema.gov</a>.



# **LEGEND**

SPECIAL FLOOD HAZARD AREAS SUBJECT TO INUNDATION BY THE 1% ANNUAL CHANCE FLOOD

The 1% annual flood (100-year flood), also known as the base flood, is the flood that has a 1% chance of being equaled or exceeded in any given year. The Special Flood Hazard Area is the area subject to flooding by the 1% annual chance flood. Areas of Special Flood Hazard include Zones A, AE, AH, AO, AR, A99, V, and VE. The Base Flood Elevation is the water-surface elevation of the 1% annual chance flood.

ZONE A No Base Flood Elevations determined.

ZONE AE Base Flood Elevations determined.

ZONE AH Flood depths of 1 to 3 feet (usually areas of ponding); Base Flood

Elevations determined.

indicates that the former flood control system is being restored to provide protection from the 1% annual chance or greater flood.

ONE A99

Area to be protected from 1% annual chance flood by a Federal flood protection system under construction; no Base Flood Elevations

Coastal flood zone with velocity hazard (wave action); no Base Flood

ZONE VE Coastal flood zone with velocity hazard (wave action); Base Flood Elevations determined.

FLOODWAY AREAS IN ZONE AE

The floodway is the channel of a stream plus any adjacent floodplain areas that must be kept free of encroachment so that the 1% annual chance flood can be carried without substantial increases in flood heights.

OTHER FLOOD AREAS

ZONE X

Areas of 0.2% annual chance flood; areas of 1% annual chance flood with average depths of less than 1 foot or with drainage areas less than 1 square mile; and areas protected by levees from 1% annual chance flood.

OTHER AREAS

ZONE X Areas determined

Areas determined to be outside the 0.2% annual chance floodplain.

Areas in which flood hazards are undetermined, but possible.

COASTAL BARRIER RESOURCES SYSTEM (CBRS) AREAS

OTHERWISE PROTECTED AREAS (OPAs)

CBRS areas and OPAs are normally located within or adjacent to Special Flood Hazard Areas.

1% annual chance floodplain boundary

 0.2% annual chance floodplain boundary

0.2% annual chance floodplain bounds
 Floodway boundary

Zone D boundary

Boundary dividing Special Flood Hazard Area Zones and boundary dividing Special Flood Hazard Areas of different Base

Flood Elevations, flood depths or flood velocities.

Base Flood Elevation line and value; elevation in feet\*

(EL 987)

Base Flood Elevation value where uniform within zone; elevation in feet\*

\* Referenced to the North American Vertical Datum of 1988

Cross section line

Limited detail cross section line

23 — — — — — 23 Transect line

87°07'45", 32°22'30" Geographic coordinates referenced to the North American Datum of 1983 (NAD 83), Western Hemisphere

1000-meter Universal Transverse Mercator grid values, zone 18N
 5000-foot grid ticks: New York State Plane coordinate system, West zone (FIPSZONE 3103), Transverse Mercator projection

DX5510 x

Bench mark (see explanation in Notes to Users section of this FIRM panel)

• M1.5

River Mile

MAP REPOSITORY
Refer to listing of Map Repositories on Map Index

EFFECTIVE DATE OF COUNTYWIDE FLOOD INSURANCE RATE MAP August 28, 2008

EFFECTIVE DATE(S) OF REVISION(S) TO THIS PANEL

For community map revision history prior to countywide mapping, refer to the Community

Map History table located in the Flood Insurance Study report for this jurisdiction.

To determine if flood insurance is available in this community, contact your Insurance agent or call the National Flood Insurance Program at 1-800-638-6620.

MAP SCALE 1" = 500'
0 500 1000
FEET

250 0 500 1000

250 0 500 METERS

0 150 300



# PANEL 0232G

# FLOOD INSURANCE RATE MAP

for MONROE COUNTY, NEW YORK (ALL JURISDICTIONS)

CONTAINS:

COMMUNITY
WEBSTER, TOWN OF
WEBSTER, VILLAGE OF

PANEL 232 OF 528

MAP SUFFIX: G

(SEE MAP INDEX FOR FIRM PANEL LAYOUT)

Notice to User: The **Map Number** shown below should be used when placing map orders; the **Community Number** shown above should be used on insurance applications for the subject community.



EFFECTIVE DATE AUGUST 28, 2008

MAP NUMBER

36055C0232G

**NUMBER** 

360436

This map is for use in administering the National Flood Insurance Program. It does not necessarily identify all areas subject to flooding, particularly from local drainage sources of small size. The community map repository should be consulted for possible updated or additional flood hazard information.

To obtain more detailed information in areas where Base Flood Elevations (BFEs) and/or floodways have been determined, users are encouraged to consult the Flood Profiles and Floodway Data and/or Summary of Stillwater Elevations tables contained within the Flood Insurance Study (FIS) report that accompanies this FIRM. Users should be aware that BFEs shown on the FIRM represent rounded whole-foot elevations. These BFEs are intended for flood insurance rating purposes only and should not be used as the sole source of flood elevation information. Accordingly, flood elevation data presented in the FIS report should be utilized in conjunction with the FIRM for purposes of construction and/or floodplain management.

Coastal Base Flood Elevations shown on this map apply only landward of 0.0' North American Vertical Datum of 1988 (NAVD 88). Users of this FIRM should be aware that coastal flood elevations are also provided in the Summary of Stillwater Elevations tables in the Flood Insurance Study report for this jurisdiction. Elevations shown in the Summary of Stillwater Elevations tables should be used for construction and/or floodplain management purposes when they are higher than the elevations shown on this FIRM.

Boundaries of the **floodways** were computed at cross sections and interpolated between cross sections. The floodways were based on hydraulic considerations with regard to requirements of the National Flood Insurance Program. Floodway widths and other pertinent floodway data are provided in the Flood Insurance Study report for this jurisdiction.

Certain areas not in Special Flood Hazard Areas may be protected by flood control structures. Refer to Section 2.4 "Flood Protection Measures" of the Flood Insurance Study report for information on flood control structures for this

The **projection** used in the preparation of this map was Universal Transverse Mercator (UTM) zone 18N. The horizontal datum was NAD 83, GRS80 spheroid. Differences in datum, spheroid, projection or UTM zones used in the production of FIRMs for adjacent jurisdictions may result in slight positional differences in map features across jurisdiction boundaries. These differences do not affect the accuracy of this FIRM.

Flood elevations on this map are referenced to the North American Vertical Datum of 1988. These flood elevations must be compared to structure and ground elevations referenced to the same vertical datum. For information regarding conversion between the National Geodetic Vertical Datum of 1929 and the North American Vertical Datum of 1988, visit the National Geodetic Survey website at <a href="http://www.ngs.noaa.gov">http://www.ngs.noaa.gov</a> or contact the National Geodetic Survey at the following address:

NGS Information Services NOAA, N/NGS12 National Geodetic Survey SSMC-3, #9202 1315 East-West Highway Silver Spring, Maryland 20910-3182 (301) 713-3242

To obtain current elevation, description, and/or location information for bench marks shown on this map, please contact the Information Services Branch of the National Geodetic Survey at (301) 713-3242, or visit its website at http://www.ngs.noaa.gov.

Base map information shown on this FIRM was derived from digital orthophotography provided by the New York State Office of Cyber Security & Critical Infrastructure Coordination. This information was provided as 30centimeter and 60-centimeter resolution natural color orthoimagery from photography dated April-May 2004


Based on updated topographic information, this map reflects more detailed and up-to-date stream channel configurations and floodplain delineations than those shown on the previous FIRM for this jurisdiction. As a result, the Flood Profiles and Floodway Data tables in the Flood Insurance Study Report (which contains authoritative hydraulic data) may reflect stream channel distances that differ from what is shown on this map. Also, the road to floodplain relationships for unrevised streams may differ from what is shown on previous maps.

Corporate limits shown on this map are based on the best data available at the time of publication. Because changes due to annexations or de-annexations may have occurred after this map was published, map users should contact appropriate community officials to verify current corporate limit locations.

Please refer to the separately printed Map Index for an overview map of the county showing the layout of map panels; community map repository addresses; and a Listing of Communities table containing National Flood Insurance Program dates for each community as well as a listing of the panels on which each community is located.

Contact the FEMA Map Service Center at 1-800-358-9616 for information on available products associated with this FIRM. Available products may include previously issued Letters of Map Change, a Flood Insurance Study report, and/or digital versions of this map. The FEMA Map Service Center may also be reached by Fax at 1-800-358-9620 and its website at http://msc.fema.gov.

If you have questions about this map or questions concerning the National Flood Insurance Program in general, please call 1-877-FEMA MAP (1-877-336-2627) or visit the FEMA website at <a href="http://www.fema.gov.">http://www.fema.gov.</a>



# **LEGEND**

SPECIAL FLOOD HAZARD AREAS SUBJECT TO INUNDATION BY THE 1% ANNUAL CHANCE FLOOD

The 1% annual flood (100-year flood), also known as the base flood, is the flood that has a 1%

chance of being equaled or exceeded in any given year. The Special Flood Hazard Area is the area subject to flooding by the 1% annual chance flood. Areas of Special Flood Hazard include Zones A, AE, AH, AO, AR, A99, V, and VE. The Base Flood Elevation is the water-surface elevation of the 1% annual chance flood.

No Base Flood Elevations determined.

Base Flood Elevations determined.

Flood depths of 1 to 3 feet (usually areas of ponding); Base Flood ZONE AH Elevations determined.

Flood depths of 1 to 3 feet (usually sheet flow on sloping terrain); average depths determined. For areas of alluvial fan flooding, velocities also

Special Flood Hazard Area formerly protected from the 1% annual chance ZONE AR flood by a flood control system that was subsequently decertified. Zone AR indicates that the former flood control system is being restored to provide

protection from the 1% annual chance or greater flood. Area to be protected from 1% annual chance flood by a Federal flood protection system under construction; no Base Flood Elevations

Coastal flood zone with velocity hazard (wave action); no Base Flood Elevations determined.

Coastal flood zone with velocity hazard (wave action); Base Flood Elevations determined.

FLOODWAY AREAS IN ZONE AE

The floodway is the channel of a stream plus any adjacent floodplain areas that must be kept free of encroachment so that the 1% annual chance flood can be carried without substantial increases

OTHER FLOOD AREAS ZONE X Areas of 0.2% annual chance flood; areas of 1% annual chance flood with

average depths of less than 1 foot or with drainage areas less than 1 square mile; and areas protected by levees from 1% annual chance flood.

in flood heights.

ZONE X

OTHER AREAS Areas determined to be outside the 0.2% annual chance floodplain.

Areas in which flood hazards are undetermined, but possible.

COASTAL BARRIER RESOURCES SYSTEM (CBRS) AREAS

OTHERWISE PROTECTED AREAS (OPAs)

CBRS areas and OPAs are normally located within or adjacent to Special Flood Hazard Areas.

1% annual chance floodplain boundary 0.2% annual chance floodplain boundary

Floodway boundary

Zone D boundary CBRS and OPA boundary ......

> Boundary dividing Special Flood Hazard Area Zones and boundary dividing Special Flood Hazard Areas of different Base Flood Elevations, flood depths or flood velocities.

~~~ 513 ~~~ Base Flood Elevation value where uniform within zone; elevation

Base Flood Elevation line and value; elevation in feet\*

\* Referenced to the North American Vertical Datum of 1988

Cross section line

Limited detail cross section line

23)-----(23) Transect line

Geographic coordinates referenced to the North American Datum 87°07'45", 32°22'30"

of 1983 (NAD 83), Western Hemisphere 1000-meter Universal Transverse Mercator grid values, zone 18N

Bench mark (see explanation in Notes to Users section of this

5000-foot grid ticks: New York State Plane coordinate system,

West zone (FIPSZONE 3103), Transverse Mercator projection

DX5510

• M1.5

MAP REPOSITORY Refer to listing of Map Repositories on Map Index

EFFECTIVE DATE OF COUNTYWIDE

FLOOD INSURANCE RATE MAP August 28, 2008

EFFECTIVE DATE(S) OF REVISION(S) TO THIS PANEL

For community map revision history prior to countywide mapping, refer to the Community Map History table located in the Flood Insurance Study report for this jurisdiction.

To determine if flood insurance is available in this community, contact your Insurance

agent or call the National Flood Insurance Program at 1-800-638-6620.

# FLOOD INSURANCE RATE MAP for MONROE COUNTY, NEW YORK (ALL JURISDICTIONS) CONTAINS: **NUMBER**

PANEL 0231G

**COMMUNITY** 

置

WEBSTER, TOWN OF WEBSTER, VILLAGE OF

PANEL 231 OF 528 MAP SUFFIX: G (SEE MAP INDEX FOR FIRM PANEL LAYOUT)

Notice to User: The Map Number shown below should be used when placing map orders; the Community Number shown above should be used on insurance applications for the



**EFFECTIVE DATE AUGUST 28, 2008** 

MAP NUMBER

36055C0231G

360436

This map is for use in administering the National Flood Insurance Program. It does not necessarily identify all areas subject to flooding, particularly from local drainage sources of small size. The community map repository should be consulted for possible updated or additional flood hazard information.

To obtain more detailed information in areas where Base Flood Elevations (BFEs) and/or floodways have been determined, users are encouraged to consult the Flood Profiles and Floodway Data and/or Summary of Stillwater Elevations tables contained within the Flood Insurance Study (FIS) report that accompanies this FIRM. Users should be aware that BFEs shown on the FIRM represent rounded whole-foot elevations. These BFEs are intended for flood insurance rating purposes only and should not be used as the sole source of flood elevation information. Accordingly, flood elevation data presented in the FIS report should be utilized in conjunction with the FIRM for purposes of construction and/or floodplain management.

Coastal Base Flood Elevations shown on this map apply only landward of 0.0' North American Vertical Datum of 1988 (NAVD 88). Users of this FIRM should be aware that coastal flood elevations are also provided in the Summary of Stillwater Elevations tables in the Flood Insurance Study report for this jurisdiction. Elevations shown in the Summary of Stillwater Elevations tables should be used for construction and/or floodplain management purposes when they are higher than the elevations shown on this FIRM.

Boundaries of the **floodways** were computed at cross sections and interpolated between cross sections. The floodways were based on hydraulic considerations with regard to requirements of the National Flood Insurance Program. Floodway widths and other pertinent floodway data are provided in the Flood Insurance Study report for this jurisdiction.

Certain areas not in Special Flood Hazard Areas may be protected by flood control structures. Refer to Section 2.4 "Flood Protection Measures" of the Flood Insurance Study report for information on flood control structures for this

The projection used in the preparation of this map was Universal Transverse Mercator (UTM) zone 18N. The horizontal datum was NAD 83, GRS80 spheroid. Differences in datum, spheroid, projection or UTM zones used in the production of FIRMs for adjacent jurisdictions may result in slight positional differences in map features across jurisdiction boundaries. These differences do not affect the accuracy of this FIRM.

Flood elevations on this map are referenced to the North American Vertical Datum of 1988. These flood elevations must be compared to structure and ground elevations referenced to the same vertical datum. For information regarding conversion between the National Geodetic Vertical Datum of 1929 and the North American Vertical Datum of 1988, visit the National Geodetic Survey website at <a href="http://www.ngs.noaa.gov">http://www.ngs.noaa.gov</a> or contact the National Geodetic Survey at the following address:

NGS Information Services NOAA, N/NGS12 National Geodetic Survey SSMC-3, #9202 1315 East-West Highway Silver Spring, Maryland 20910-3182 (301) 713-3242

To obtain current elevation, description, and/or location information for bench marks shown on this map, please contact the Information Services Branch of the National Geodetic Survey at (301) 713-3242, or visit its website at http://www.ngs.noaa.gov.

Base map information shown on this FIRM was derived from digital orthophotography provided by the New York State Office of Cyber Security & Critical Infrastructure Coordination. This information was provided as 30centimeter and 60-centimeter resolution natural color orthoimagery from photography dated April-May 2004


Based on updated topographic information, this map reflects more detailed and up-to-date stream channel configurations and floodplain delineations than those shown on the previous FIRM for this jurisdiction. As a result, the Flood Profiles and Floodway Data tables in the Flood Insurance Study Report (which contains authoritative hydraulic data) may reflect stream channel distances that differ from what is shown on this map. Also, the road to floodplain relationships for unrevised streams may differ from what is shown on previous maps.

Corporate limits shown on this map are based on the best data available at the time of publication. Because changes due to annexations or de-annexations may have occurred after this map was published, map users should contact appropriate community officials to verify current corporate limit locations.

Please refer to the separately printed Map Index for an overview map of the county showing the layout of map panels; community map repository addresses; and a Listing of Communities table containing National Flood Insurance Program dates for each community as well as a listing of the panels on which each community is located.

Contact the FEMA Map Service Center at 1-800-358-9616 for information on available products associated with this FIRM. Available products may include previously issued Letters of Map Change, a Flood Insurance Study report, and/or digital versions of this map. The FEMA Map Service Center may also be reached by Fax at 1-800-358-9620 and its website at http://msc.fema.gov.

If you have questions about this map or questions concerning the National Flood Insurance Program in general, please call 1-877-FEMA MAP (1-877-336-2627) or visit the FEMA website at <a href="http://www.fema.gov.">http://www.fema.gov.</a>



## **LEGEND**

ZONE AR

ZONE X

SPECIAL FLOOD HAZARD AREAS SUBJECT TO INUNDATION BY THE 1% ANNUAL CHANCE FLOOD

The 1% annual flood (100-year flood), also known as the base flood, is the flood that has a 1% chance of being equaled or exceeded in any given year. The Special Flood Hazard Area is the area subject to flooding by the 1% annual chance flood. Areas of Special Flood Hazard include Zones A, AE, AH, AO, AR, A99, V, and VE. The Base Flood Elevation is the water-surface elevation of the 1% annual chance flood.

No Base Flood Elevations determined. Base Flood Elevations determined. Flood depths of 1 to 3 feet (usually areas of ponding); Base Flood ZONE AH Elevations determined. Flood depths of 1 to 3 feet (usually sheet flow on sloping terrain); average

> Special Flood Hazard Area formerly protected from the 1% annual chance flood by a flood control system that was subsequently decertified. Zone AR indicates that the former flood control system is being restored to provide

depths determined. For areas of alluvial fan flooding, velocities also

protection from the 1% annual chance or greater flood. Area to be protected from 1% annual chance flood by a Federal flood protection system under construction; no Base Flood Elevations

Coastal flood zone with velocity hazard (wave action); no Base Flood Elevations determined.

Coastal flood zone with velocity hazard (wave action); Base Flood Elevations determined.

FLOODWAY AREAS IN ZONE AE

The floodway is the channel of a stream plus any adjacent floodplain areas that must be kept free of encroachment so that the 1% annual chance flood can be carried without substantial increases in flood heights.

OTHER FLOOD AREAS

ZONE X Areas of 0.2% annual chance flood; areas of 1% annual chance flood with average depths of less than 1 foot or with drainage areas less than 1 square mile; and areas protected by levees from 1% annual chance flood.

OTHER AREAS

Areas determined to be outside the 0.2% annual chance floodplain. Areas in which flood hazards are undetermined, but possible.

COASTAL BARRIER RESOURCES SYSTEM (CBRS) AREAS

OTHERWISE PROTECTED AREAS (OPAs)

CBRS areas and OPAs are normally located within or adjacent to Special Flood Hazard Areas. 1% annual chance floodplain boundary

0.2% annual chance floodplain boundary

Floodway boundary Zone D boundary

CBRS and OPA boundary ......

Boundary dividing Special Flood Hazard Area Zones and boundary dividing Special Flood Hazard Areas of different Base Flood Elevations, flood depths or flood velocities.

Base Flood Elevation line and value; elevation in feet\* ~~~ 513 ~~~ Base Flood Elevation value where uniform within zone; elevation

\* Referenced to the North American Vertical Datum of 1988

Cross section line

Limited detail cross section line

23-----23 Geographic coordinates referenced to the North American Datum 87°07'45", 32°22'30"

of 1983 (NAD 83), Western Hemisphere 1000-meter Universal Transverse Mercator grid values, zone 18N

5000-foot grid ticks: New York State Plane coordinate system, West zone (FIPSZONE 3103), Transverse Mercator projection

Bench mark (see explanation in Notes to Users section of this DX5510

• M1.5

MAP REPOSITORY

Refer to listing of Map Repositories on Map Index EFFECTIVE DATE OF COUNTYWIDE

FLOOD INSURANCE RATE MAP August 28, 2008

EFFECTIVE DATE(S) OF REVISION(S) TO THIS PANEL

For community map revision history prior to countywide mapping, refer to the Community Map History table located in the Flood Insurance Study report for this jurisdiction.

To determine if flood insurance is available in this community, contact your Insurance

agent or call the National Flood Insurance Program at 1-800-638-6620.

HHH

# FLOOD INSURANCE RATE MAP (ALL JURISDICTIONS) CONTAINS: COMMUNITY WEBSTER, TOWN OF PANEL 233 OF 528 MAP SUFFIX: G

MITTONNIAL

# PANEL 0233G

for MONROE COUNTY, NEW YORK

**NUMBER** PENFIELD, TOWN OF

360436 WEBSTER, VILLAGE OF

(SEE MAP INDEX FOR FIRM PANEL LAYOUT)

Notice to User: The Map Number shown below should be used when placing map orders; the Community Number shown above should be used on insurance applications for the



36055C0233G **EFFECTIVE DATE** 

MAP NUMBER

360426

**AUGUST 28, 2008** 

This map is for use in administering the National Flood Insurance Program. It does not necessarily identify all areas subject to flooding, particularly from local drainage sources of small size. The community map repository should be consulted for possible updated or additional flood hazard information.

To obtain more detailed information in areas where Base Flood Elevations (BFEs) and/or floodways have been determined, users are encouraged to consult the Flood Profiles and Floodway Data and/or Summary of Stillwater Elevations tables contained within the Flood Insurance Study (FIS) report that accompanies this FIRM. Users should be aware that BFEs shown on the FIRM represent rounded whole-foot elevations. These BFEs are intended for flood insurance rating purposes only and should not be used as the sole source of flood elevation information. Accordingly, flood elevation data presented in the FIS report should be utilized in conjunction with the FIRM for purposes of construction and/or floodplain management.

Coastal Base Flood Elevations shown on this map apply only landward of 0.0' North American Vertical Datum of 1988 (NAVD 88). Users of this FIRM should be aware that coastal flood elevations are also provided in the Summary of Stillwater Elevations tables in the Flood Insurance Study report for this jurisdiction. Elevations shown in the Summary of Stillwater Elevations tables should be used for construction and/or floodplain management purposes when they are higher than the elevations shown on this FIRM.

Boundaries of the **floodways** were computed at cross sections and interpolated between cross sections. The floodways were based on hydraulic considerations with regard to requirements of the National Flood Insurance Program. Floodway widths and other pertinent floodway data are provided in the Flood Insurance Study report for this jurisdiction.

Certain areas not in Special Flood Hazard Areas may be protected by flood control structures. Refer to Section 2.4 "Flood Protection Measures" of the Flood Insurance Study report for information on flood control structures for this

The projection used in the preparation of this map was Universal Transverse Mercator (UTM) zone 18N. The horizontal datum was NAD 83, GRS80 spheroid. Differences in datum, spheroid, projection or UTM zones used in the production of FIRMs for adjacent jurisdictions may result in slight positional differences in map features across jurisdiction boundaries. These differences do not affect the accuracy of this FIRM.

Flood elevations on this map are referenced to the North American Vertical Datum of 1988. These flood elevations must be compared to structure and ground elevations referenced to the same vertical datum. For information regarding conversion between the National Geodetic Vertical Datum of 1929 and the North American Vertical Datum of 1988, visit the National Geodetic Survey website at <a href="http://www.ngs.noaa.gov">http://www.ngs.noaa.gov</a> or contact the National Geodetic Survey at the following address:

NGS Information Services NOAA, N/NGS12 National Geodetic Survey SSMC-3, #9202 1315 East-West Highway Silver Spring, Maryland 20910-3182 (301) 713-3242

To obtain current elevation, description, and/or location information for bench marks shown on this map, please contact the Information Services Branch of the National Geodetic Survey at (301) 713-3242, or visit its website at http://www.ngs.noaa.gov.

Base map information shown on this FIRM was derived from digital orthophotography provided by the New York State Office of Cyber Security & Critical Infrastructure Coordination. This information was provided as 30centimeter and 60-centimeter resolution natural color orthoimagery from photography dated April-May 2004


Based on updated topographic information, this map reflects more detailed and up-to-date stream channel configurations and floodplain delineations than those shown on the previous FIRM for this jurisdiction. As a result, the Flood Profiles and Floodway Data tables in the Flood Insurance Study Report (which contains authoritative hydraulic data) may reflect stream channel distances that differ from what is shown on this map. Also, the road to floodplain relationships for unrevised streams may differ from what is shown on previous maps.

Corporate limits shown on this map are based on the best data available at the time of publication. Because changes due to annexations or de-annexations may have occurred after this map was published, map users should contact appropriate community officials to verify current corporate limit locations.

Please refer to the separately printed Map Index for an overview map of the county showing the layout of map panels; community map repository addresses; and a Listing of Communities table containing National Flood Insurance Program dates for each community as well as a listing of the panels on which each community is located.

Contact the FEMA Map Service Center at 1-800-358-9616 for information on available products associated with this FIRM. Available products may include previously issued Letters of Map Change, a Flood Insurance Study report, and/or digital versions of this map. The FEMA Map Service Center may also be reached by Fax at 1-800-358-9620 and its website at http://msc.fema.gov.

If you have questions about this map or questions concerning the National Flood Insurance Program in general, please call 1-877-FEMA MAP (1-877-336-2627) or visit the FEMA website at <a href="http://www.fema.gov.">http://www.fema.gov.</a>



# **LEGEND**

SPECIAL FLOOD HAZARD AREAS SUBJECT TO INUNDATION BY THE 1% ANNUAL CHANCE FLOOD

The 1% annual flood (100-year flood), also known as the base flood, is the flood that has a 1% chance of being equaled or exceeded in any given year. The Special Flood Hazard Area is the area subject to flooding by the 1% annual chance flood. Areas of Special Flood Hazard include Zones A, AE, AH, AO, AR, A99, V, and VE. The Base Flood Elevation is the water-surface elevation of the 1% annual chance flood.

No Base Flood Elevations determined. Base Flood Elevations determined.

ZONE AH Flood depths of 1 to 3 feet (usually areas of ponding); Base Flood Elevations determined.

Special Flood Hazard Area formerly protected from the 1% annual chance ZONE AR flood by a flood control system that was subsequently decertified. Zone AR indicates that the former flood control system is being restored to provide

Flood depths of 1 to 3 feet (usually sheet flow on sloping terrain); average

depths determined. For areas of alluvial fan flooding, velocities also

Area to be protected from 1% annual chance flood by a Federal flood protection system under construction; no Base Flood Elevations

protection from the 1% annual chance or greater flood.

Coastal flood zone with velocity hazard (wave action); no Base Flood Elevations determined.

Coastal flood zone with velocity hazard (wave action); Base Flood Elevations determined.

FLOODWAY AREAS IN ZONE AE

The floodway is the channel of a stream plus any adjacent floodplain areas that must be kept free of encroachment so that the 1% annual chance flood can be carried without substantial increases in flood heights.

OTHER FLOOD AREAS ZONE X Areas of 0.2% annual chance flood; areas of 1% annual chance flood with

average depths of less than 1 foot or with drainage areas less than 1 square mile; and areas protected by levees from 1% annual chance flood.

OTHER AREAS

ZONE X Areas determined to be outside the 0.2% annual chance floodplain.

Areas in which flood hazards are undetermined, but possible. COASTAL BARRIER RESOURCES SYSTEM (CBRS) AREAS

OTHERWISE PROTECTED AREAS (OPAs)

CBRS areas and OPAs are normally located within or adjacent to Special Flood Hazard Areas.

1% annual chance floodplain boundary 0.2% annual chance floodplain boundary

Floodway boundary

Zone D boundary CBRS and OPA boundary ...... Boundary dividing Special Flood Hazard Area Zones and

boundary dividing Special Flood Hazard Areas of different Base Flood Elevations, flood depths or flood velocities. Base Flood Elevation line and value; elevation in feet\* ~~~ 513 ~~~

Base Flood Elevation value where uniform within zone; elevation

\* Referenced to the North American Vertical Datum of 1988 Cross section line

Limited detail cross section line

23)-----(23) Geographic coordinates referenced to the North American Datum 87°07'45", 32°22'30"

of 1983 (NAD 83), Western Hemisphere 1000-meter Universal Transverse Mercator grid values, zone 18N

5000-foot grid ticks: New York State Plane coordinate system, West zone (FIPSZONE 3103), Transverse Mercator projection

DX5510 Bench mark (see explanation in Notes to Users section of this

• M1.5

MAP REPOSITORY Refer to listing of Map Repositories on Map Index


EFFECTIVE DATE OF COUNTYWIDE FLOOD INSURANCE RATE MAP August 28, 2008

EFFECTIVE DATE(S) OF REVISION(S) TO THIS PANEL

For community map revision history prior to countywide mapping, refer to the Community

Map History table located in the Flood Insurance Study report for this jurisdiction.

To determine if flood insurance is available in this community, contact your Insurance agent or call the National Flood Insurance Program at 1-800-638-6620.



PANEL 0234G


# FLOOD INSURANCE RATE MAP for MONROE COUNTY, NEW YORK (ALL JURISDICTIONS) **CONTAINS**: **NUMBER**

COMMUNITY

PENFIELD, TOWN OF WEBSTER, TOWN OF

PANEL 234 OF 528 MAP SUFFIX: G

(SEE MAP INDEX FOR FIRM PANEL LAYOUT) Notice to User: The Map Number shown below should be used when placing map orders; the Community Number shown above should be used on insurance applications for the



36055C0234G **EFFECTIVE DATE** 


MAP NUMBER

360426

360436

#### **ELEVATION REFERENCE MARKS** REFERENCE ELEVATION DESCRIPTION OF LOCATION REFERENCE ELEVATION DESCRIPTION OF LOCATION (FEET NGVD) MARK (FEET NGVD) MARK 312.50 A standard N.Y. Geodetic Survey disk set in concrete located 26 feet east of centerline on County Line 451.09 A standard U.S. Coast & Geodetic Survey disk stamped "F147 1942" located in top of north end of east headwall for culvert on Lincoln Road approximately 160 feet south of Lincoln Road intersection with Road about 160 feet south of intersection with Lake Road, 84 feet south of 16-inch elm, 64,5 feet east of intersection of west right of way fence of County Line Road with south right of way fence of cut-off road. 307.6 Point in payement on centerline of Lake Road opposite drive, approximately 3450 feet east of Lake Road Point in pavement on centerline of Lincoln Road opposite farm road about 1050 feet north of Lincoln Road and County Line Road intersection. intersection with Clevenger Road. Point in pavement on centerline of Lake Road at intersection with Roder Parkway. A standard U.S. Coast & Geodetic Survey disk stamped "G147 1942" located in top of south end of west headwall at intersection of Lincoln Road and Clevenger Road. A standard U.S. Coast & Geodetic Survey disk stamped "K149 1942" set in top of concrete post located at intersection of Lake Road and Verdine Road, 53 feet east of Verdine Road, 25 feet north of Lake Road, Point in pavement on centerline of Whitney Road at intersection with Swadling Road. 24 feet west of a white walnut tree. Point in pavement on centerline of Slocum Road at intersection with Clevenger Road. 282.51 A standard U.S. Coast & Geodetic Survey disk stamped "J149 1942" set in top of concrete post located Point in pavement on centerline of Clevenger Road opposite driveway, approximately 2930 feet west of 29 feet south of Lake Road, approximately 1350 feet east of Lake Road and Slocum Road, about 200 Clevenger Road intersection with Slocum Road. feet west of a small culvert. 422.09 A standard U.S. Coast & Geodetic Survey disk stamped "F152 1942" located along Conrail approximately 1800 feet east of intersection of Slocum Road and U.S. Highway 104, 270 feet east of Conrail milepost 78, Point in payement on centerline of Lakeside Road opposite drive, approximately 1700 feet south of Lakeside Road and Lake Road intersection. 48 feet north of track, 150 feet west of farm road crossing. 351.73 A standard U.S. Coast & Geodetic Survey disk stamped "L149 1942" set in top of south end of west Point in pavement on centerline of Slocum Road opposite driveway, approximately 2000 feet north of headwall for culvert on Lakeside Road approximately 800 feet north of Lakeside Road intersection with Slocum Road intersection with U.S. Highway 104. Boston Road, 15 feet west of Lakeside Road. Point on centerline of Conrail tracks, over a culvert, approximately 1450 feet east of Lakeside Road Point in payement on centerline of Willits Road opposite driveway approximately 800 feet east of Willits intersection with U.S. Highway 104. Road intersection with Lakeside Road. Point in pavement on centerline of Slocum Road at intersection with Willits Road. 385.47 A standard N.Y. Geodetic Survey disk located 18.5 feet west of centerline on County Line Road about 270 feet south of intersection with Berge Road, 81 feet west of telephone pole on east side of road. 384.29 A standard U.S. Coast & Geodetic Survey disk stamped "M149 1942" located in top of west wingwall of Point on centerline of Conrail tracks, over center of bridge, apprint 1350 feet east of County Line north abutinent of the Lakeside Road bridge over Mill Creek, 15 feet west of road, 1.4 feet west of guard rail, about \$80 feet north of intersection with Berge Road. Point in pavement on centerline of Slocum Road opposite farm road, approximately 2100 feet south of Point in pavement on centerline of driveway on east side of Lakeside Road, over culvert, about 1680 feet north of Lakeside Road intersection with U.S. Highway 104. Slocum Road intersection with Lake Road. 423.59 A standard U.S. Coast & Geodetic Survey disk stamped "N149 1942" located level with track along Conrail at crossing of Lakeside Road, 47.5 feet north of track, 30 feet west of Lakeside Road, 3.5 feet west of

Conrail milepost 79.



**KEY TO MAP** 500-Year Flood Boundary-

100-Year Flood Boundary Zone Designations\* With Date of Identification e.g., 2/2/74

100-Year Flood Boundary

500-Year Flood Boundary-<del>-----513-----</del>

(EL 987)

RM7×

• M1.5

Base Flood Elevation Line With Elevation In Feet\*\* Base Flood Elevation in Feet Where Uniform Within Zone\*\*

Elevation Reference Mark

River Mile

\*\*Referenced to the National Geodetic Vertical Datum of 1929

\*EXPLANATION OF ZONE DESIGNATIONS

**EXPLANATION** Areas of 100-year flood; base flood elevations and flood hazard factors not determined.

Areas of 100-year shallow flooding where depths are between one (1) and three (3) feet; average depths of inundation are shown, but no flood hazard factors

Areas of 100-year shallow flooding where depths are between one (1) and three (3) feet; base flood elevations are shown, but no flood hazard factors

A1-A30 Areas of 100-year flood; base flood elevations and flood hazard factors determined.

Areas of 100-year flood to be protected by flood protection system under construction; base flood elevations and flood hazard factors not determined. Areas between limits of the 100-year flood and 500year flood; or certain areas subject to 100-year flooding with average depths less than one (1) foot or where

the contributing drainage area is less than one square mile; or areas protected by levees from the base flood. Areas of minimal flooding. (No shading) Areas of undetermined, but possible, flood hazards.

Areas of 100-year coastal flood with velocity (wave action); base flood elevations and flood hazard factors

V1-V30 Areas of 100-year coastal flood with velocity (wave action); base flood elevations and flood hazard factors determined.

NOTES TO USER

Certain areas not in the special flood hazard areas (zones A and V) may be protected by flood control structures. This map is for flood insurance purposes only; it does not neces-

sarily show all areas subject to flooding in the community or all planimetric features outside special flood hazard areas. For adjoining map panels, see separately printed Index To Map

> INITIAL IDENTIFICATION MAY 31, 1974 AUGUST 20, 1976

CONVERSION TO REGULAR PROGRAM JUNE 1, 1978

To determine if flood insurance is available in this community, contact your insurance agent, or call the National Flood Insurance Program, at (800) 638-6620, or (800) 424-8872.

APPROXIMATE SCALE

NATIONAL FLOOD INSURANCE PROGRAM

FLOOD INSURANCE RATE MAP

TOWN OF ONTARIO, NEW YORK WAYNE COUNTY


COMMUNITY-PANEL NUMBER 360895 0005 B

PAGE 5 OF 10

EFFECTIVE

JUNE 1, 1978

AND URBAN DEVELOPMENT FEDERAL INSURANCE ADMINISTRATION



| ELEVATION | REFERENCE | MARKS |  |
|-----------|-----------|-------|--|
|           |           |       |  |

| REFERENCE<br>MARK | ELEVATION<br>(FEET NGVD | - LOCATION C. LOCATION                                                                                                                                                                                                                                           | REFERENCE<br>MARK | ELEVATION<br>(FEET NGVD) | DESCRIPTION OF LOCATION                                                                                                                                                                                     |  |
|-------------------|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| RM25              | 260.1                   | Point in pavement on centerline of Ginna Access Road at bridge over Mill Creek, approximately 1120 feet north of Lake Road.                                                                                                                                      | RM33              | 270.4                    | Point in pavement on centerline of Town Line Road, over culvert, about 100 feet south of Lake Road.                                                                                                         |  |
| RM26              | 325.81                  | A standard U.S. Coast & Geodetic Survey disk stamped "H149 1942" set in top of concrete post located on Lake Road about 550 feet east of intersection of Lake Road with Ontario Center Road, at Brookwood                                                        | RM34              | 315.2                    | Point in pavement on centerline of Furnaceville Road opposite utility pole, approximately 2400 feet south of Furnaceville Road intersection with Lake Road.                                                 |  |
| RM27              | 274.4                   | Farm, 22 feet west of road, 18 feet west of large stone gatepost.                                                                                                                                                                                                | RM35              | 349.3                    | Point in pavement on centerline of Furnaceville Road opposite utility pole, approximately 700 feet north of Furnaceville Road intersection with Trimble Road.                                               |  |
| nivi27            | 2/4,4                   | Point in pavement on centerline of Lake Road approximately 2240 feet east of Lake Road intersection with Ontario Center Road.                                                                                                                                    | RM36              |                          | Point in pavement on centerline of Kenyon Road, over culvert, about 1900 feet east of Kenyon Road intersection with Furnaceville Road.                                                                      |  |
| RM28              | 295.04                  | A standard U.S. Coast & Geodetic Survey disk stamped "G149 1942" located 16 feet east of Knickerbocker Road in east headwall of a culvert about 60 feet south of Lake Road.                                                                                      | RM37              | 407.86                   | A standard U.S. Coast & Geodetic Survey disk stamped "C152 1942" set in top of north headwall for                                                                                                           |  |
| RM29              | 279.8                   | Point in pavement on centerline of Lake Road opposite driveway, about 1690 feet east of Lake Road intersection with Knickerbocker Road.                                                                                                                          | RM38              | 410.0                    | 36—inch culvert beneath Conrail tracks, approximately 1950 feet east of Furnaceville Road crossing.  Point in pavement on centerline of Furnaceville Road at center of Conrail tracks located approximately |  |
| RM30              | 254.43                  | A standard U.S. Coast & Geodetic Survey disk stamped "F149 1942" located in top of south wingwall of east abutment of Lake Road bridge over Bear Creek.                                                                                                          | RM39              |                          | 170 feet north of Railroad Avenue.  Point in pavement on centerline of Walworth—Ontario Road, over culvert, approximately 650 feet south of                                                                 |  |
| RM31              | 265.3                   | Point in pavement on centerline of Lake Road at intersection with Furnaceville Road.                                                                                                                                                                             | 228.64.0          |                          | Walworth—Ontario Road intersection with Ridge Road.                                                                                                                                                         |  |
| RM32              |                         | A standard U.S. Coast & Geodetic Survey disk stamped "E149 1942" located in top of south headwall of large culvert on Lake Road, approximately 1250 feet east of Lake Road intersection with Furnaceville Road, about 75 feet west of driveway to Camp Overalls. | RM40              |                          | Point in pavement on centerline of Paddy Lane opposite driveway, about 470 feet west of Paddy Lane intersection with Walworth-Ontario Road intersection.                                                    |  |

**KEY TO MAP** 

500-Year Flood Boundary-ZONE B 100-Year Flood Boundary

100-Year Flood Boundary ZONE B

● M1.5

500-Year Flood Boundary-513---Base Flood Elevation Line With Elevation In Feet\*\* Base Flood Elevation in Feet (EL 987)

Where Uniform Within Zone\*\* Elevation Reference Mark

\*EXPLANATION OF ZONE DESIGNATIONS

\*\*Referenced to the National Geodetic Vertical Datum of 1929

**EXPLANATION** 

Areas of 100-year flood; base flood elevations and flood hazard factors not determined.

Areas of 100-year shallow flooding where depths are between one (1) and three (3) feet; average depths of inundation are shown, but no flood hazard factors are determined. AH Areas of 100-year shallow flooding where depths are between one (1) and three (3) feet; base flood elevations are shown, but no flood hazard factors

are determined. A1-A30 Areas of 100-year flood; base flood elevations and flood hazard factors determined.

Areas of 100-year flood to be protected by flood protection system under construction; base flood elevations and flood hazard factors not determined.

Areas between limits of the 100-year flood and 500-year flood; or certain areas subject to 100-year flooding with average depths less than one (1) foot or where the contributing drainage area is less than one square mile; or areas protected by levees from the base flood. (Medium shading) (Medium shading)

Areas of minimal flooding. (No shading)

Areas of undetermined, but possible, flood hazards. Areas of 100-year coastal flood with velocity (wave action); base flood elevations and flood hazard factors not determined.

V1-V30 Areas of 100-year coastal flood with velocity (wave action); base flood elevations and flood hazard factors

NOTES TO USER

Certain areas not in the special flood hazard areas (zones A and V) may be protected by flood control structures. This map is for flood insurance purposes only; it does not necessarily show all areas subject to flooding in the community or all planimetric features outside special flood hazard areas. For adjoining map panels, see separately printed Index To Map

INITIAL IDENTIFICATION

CONVERSION TO REGULAR PROGRAM

JUNE 1, 1978

To determine if flood insurance is available in this community, contact your insurance agent, or call the National Flood Insurance Program, at (800) 638-6620, or (800) 424-8872.



APPROXIMATE SCALE

1000 0

1000 FEET

NATIONAL FLOOD INSURANCE PROGRAM

FLOOD INSURANCE RATE MAP


TOWN OF ONTARIO, NEW YORK WAYNE COUNTY


COMMUNITY-PANEL NUMBER 360895 0010 B

PAGE 10 OF 10

EFFECTIVE JUNE 1, 1978

U.S. DEPARTMENT OF HOUSING AND URBAN DEVELOPMENT FEDERAL INSURANCE ADMINISTRATION





# **ELEVATION REFERENCE MARKS**

REFERENCE

| FERENCE<br>MARK | ELEVATION<br>IN FT. (NGVD) <sup>1</sup> | DESCRIPTION OF LOCATION                                                                                                                                                                                                                                                                                                                                                                                                       |
|-----------------|-----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RM 1            | 258.274                                 | D149 (United States Coast and Geodetic Survey) a standard disk, stamped "D 149 1942" located in the Town of Williamson, Wayne County, on Lake Road, approximately 1,700 feet east of Lake Road-Fisher Road intersection, at a small concrete bridge, in the top of the south wing wall of the east abutment, 16 feet south of the centerline of the road, and about 1 foot lower than the road.                               |
| RM 2            | 255.7                                   | V753 on Lake Road, Town of Williamson, Wayne County, approximately 2,700 feet west of Lake Road Stoney Lonesome Road intersection, established by study contractor in 1975. Point on centerline of Lake Road in pavement opposite road on north side of Lake Road.                                                                                                                                                            |
| RM 3            | 268.211                                 | C149 (United States Coast and Geodetic Survey), a standard disk, stamped "C 149 1942," located in the Town of Williamson, Wayne County, on Lake Road, approximately 1,170 feet east of Lake Road-Stoney Lonesome Road intersection, at the east end of a curve, at a concrete culvert, in the top of the west end of the north head wall, 18 feet north of the centerline of Lake Road, and about 2 feet lower than the road. |
| RM 4            | 270.7                                   | V755 on Lake Road, Town of Williamson, Wayne County, approximately 4,300 feet east of Lake Road-Stoney Lonesome Road intersection, established by study contractor in 1975. Point on centerline of Lake Road in pavement                                                                                                                                                                                                      |
| RM 5            | 280.757                                 | B149 (United States Coast and Geodetic Survey), a standard disk, stamped "B 149 1942," set in the top of a concrete post, located in the Town of Williamson, Wayne County, on Lake Road, approximately 6,500 feet east of Lake Road-Stoney Lonesome Road intersection, 24 feet southwest of the south end of a small culvert, 30 feet south of the centerline of Lake Road, and about level with the road.                    |
| RM 6            | 262.214                                 | Z148 (United States Coast and Geodetic Survey), a standard disk, stamped "Z148 1942," located in the Town of Williamson, Wayne County, on Mill Street, approximately 400 feet east of Mill Street-Hamilton Street intersection, at the concrete bridge over Salmon Creek, in the top of the north wing wall of the west abutment, 20 feet north of the centerline of Mill Street and about one foot higher than the road.     |
| RM 7            | 274.675                                 | Y148 (United States Coast and Geodetic Survey), a standard disk, stamped "Y148 1942," set in the top of a concrete post, located in the Town of Williamson, Wayne County, on Lake Road, approximately 1,000 feet west of Lake Road-Bear Swamp Road intersection, about 170 feet west of a small stone culvert, 27 feet north of the centerline of Lake Road, and about level with the road.                                   |
| RM 8            | 282.391                                 | X148 (United States Coast and Geodetic Survey), a standard disk, stamped "X148 1942," located in the Town of Williamson, Wayne County, on Lake Road, approximately 1,450 feet west of Lake Road-Town Line Road intersection, at a cast iron pipe culvert, in the top of the west end of the north concrete head wall, 18 feet north of the centerline of Lake Road, and about 1 foot lower than the road.                     |
| RM 9            | 274.668                                 | U149 (United States Coast and Geodetic Survey), a standard disk, stamped "U149 1942," located in the Town of Williamson, Wayne County, on Hamilton Street, approximately 50 feet south of Hamilton Street-Salmon Creek Road intersection, at the concrete bridge over Salmon Creek, in the top of the northeast wing wall, east of the road, and about 1 foot higher than the road                                            |
| RM 10           | 322.5                                   | V710A on Salmon Creek Road, Town of Williamson, Wayne County, approximately 2,300 feet southwest of Salmon Creek Road-Hamilton Street intersection, established by study contractor in 1975 Point on centerline of Salmon Creek Road in pavement                                                                                                                                                                              |
| RM 11           | 318.1                                   | V702B at the intersection of Salmon Creek Road and Tuckahoe Road, Town of Williamson, Wayne County, established by study contractor in 1975. Point on centerline of Salmon Creek Road in pavement at intersection of roads.                                                                                                                                                                                                   |
| RM 12           | 349.4                                   | V701B at the intersection of Salmon Creek Road and Eaton Road, Tow of Williamson, Wayne County, established by study contractor in 1975. Point on centerline of Salmon Creek Road in pavement at intersection of roads                                                                                                                                                                                                        |
| RM 13           | 373.1                                   | V701A on Salmon Creek Road, Town of Williamson, Wayne County, approximately 2,900 feet south of Salmon Creek Road-<br>Eaton Road intersection, established by study contractor in 1975. Point on centerline of Salmon Creek Road in pavement                                                                                                                                                                                  |
| RM 14           | 386.6                                   | V661 on Kenyon Road, Town of Williamson, Wayne County, approximately 1,150 feet west of Kenyon Road-Salmon Creek Road intersection, established by study contractor in 1975. Point on centerline of Kenyon Road in pavement of road over center of culvert for Salmon Creek tributary                                                                                                                                         |
| RM 15           | 411.125                                 | Z149 (United States Coast and Geodetic Survey), a standard disk, stamped "Z149 1942," located in the Town of Williamson, Wayne County, along CONRALL tracks, approximately 100 feet east of Salmon Creek Road crossing, in the top of the southwest wing wall of a small concrete bridge, 12 feet south of the centerline of the track and about two feet lower than the track                                                |
| RM 16           | 423.6                                   | V653B on Salmon Creek Road, Town of Williamson, Wayne County, approximately 1,600 feet north of Salmon Creek Road-Ridge Road intersection, established by Study Contractor in 1975. Point on centerline of Salmon Creek Road in the pavement on west side of the road.                                                                                                                                                        |
| RM 17           | 443.4                                   | V654A at the intersection of Ridge Road and Fernways Street, Town of Williamson, Wayne County, established by study contractor in 1975. Point on centerline of Ridge Road in the pavement at the intersection of the roads.                                                                                                                                                                                                   |
| RM 18           | 447.1                                   | V654B at the intersection of Ridge Road and Tuckahoe Road, Town of Williamson, Wayne County, established by study contractor in 1975. Point on centerline of Ridge Road in the pavement at the intersection of the roads                                                                                                                                                                                                      |
| RM 19           | 471.8                                   | V652A at the intersection of Ridge Chapel Road and Beach Road, Town of Williamson, Wayne County, established by study contractor in 1975. Point on centerline of Ridge Road in the pavement at the intersection of the roads                                                                                                                                                                                                  |

**KEY TO MAP** 

ZONE B

ZONE B

---- 513----

(EL 987)

 $RM7_{\times}$ 

500-Year Flood Boundary 100-Year Flood Boundary

Zone Designations\* With Date of Identification e.g., 12/2/74

100-Year Flood Boundary 500-Year Flood Boundary

Base Flood Elevation Line With Elevation In Feet\*\*

Base Flood Elevation in Feet Where Uniform Within Zone\*\* Elevation Reference Mark

M1.5 River Mile \*\*Referenced to the National Geodetic Vertical Datum of 1929

# \*EXPLANATION OF ZONE DESIGNATIONS

EXPLANATION Areas of 100-year flood; base flood elevations and flood hazard factors not determined.

Areas of 100-year shallow flooding where depths are between one (1) and three (3) feet; average depths of inundation are shown, but no flood hazard factors AH Areas of 100-year shallow flooding where depths are between one (1) and three (3) feet; base flood elevations are shown, but no flood hazard factors

A1-A30 Areas of 100-year flood; base flood elevations and flood hazard factors determined. Areas of 100-year flood to be protected by flood

protection system under construction; base flood elevations and flood hazard factors not determined. Areas between limits of the 100-year flood and 500-year flood; or certain areas subject to 100-year flooding with average depths less than one (1) foot or where the contributing drainage area is less than one square mile; or areas protected by levees from the base flood. (Medium shading)

(Medium shading) Areas of minimal flooding. (No shading) Areas of undetermined, but possible, flood hazards. Areas of 100-year coastal flood with velocity (wave action); base flood elevations and flood hazard factors

V1-V30 Areas of 100-year coastal flood with velocity (wave action); base flood elevations and flood hazard factors determined.

# NOTES TO USER

may be protected by flood control structures. This map is for flood insurance purposes only; it does not necessarily show all areas subject to flooding in the community or all planimetric features outside special flood hazard areas. For adjoining map panels, see separately printed Index To Map

INITIAL IDENTIFICATION
JUNE 28, 1974

CONVERSION TO REGULAR PROGRAM OCTOBER 17, 1978

Refer to the CONVERSION TO REGULAR PROGRAM date shown on this map to determine when actuarial rates apply to structures in the zones where elevations or depths have been established.

To determine if flood insurance is available in this community, contact your insurance agent, or call the National Flood Insurance Program, at (800) 638-6620, or (800) 424-8872.



APPROXIMATE SCALE 1000 FEET

NATIONAL FLOOD INSURANCE PROGRAM

FLOOD INSURANCE RATE MAP

TOWN OF WILLIAMSON, NEW YORK WAYNE COUNTY

COMMUNITY-PANEL NUMBER 360900 0010 C

PAGE 10 OF 10

(SEE MAP INDEX FOR PAGES NOT PRINTED)

OCTOBER 17, 1978


U.S. DEPARTMENT OF HOUSING AND URBAN DEVELOPMENT FEDERAL INSURANCE ADMINISTRATION



### **ELEVATION REFERENCE MARKS**

| REFERENCE<br>MARK | ELEVATION<br>IN FT. (NGVD) <sup>1</sup> | DESCRIPTION OF LOCATION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|-------------------|-----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RM 1              | 279.3                                   | V766B on Gates Drive, Town of Sodus, Wayne County, approximately 2,580 feet north of Gates Drive-Lake Road intersection, established by Study Contractor in 1975. Point on the centerline of Gates Drive at the location it changes direction from north-south to east-west.                                                                                                                                                                                                                                                                |
| RM 2              | 277.637                                 | W148 (United States Coast and Geodetic Survey), a standard disk, stamped "W148 1942," located in the Town of Sodus, Wayne County, on Lake Road approximately 300 feet west of Lake Road-Redman Road intersection, near a large house and two bank barns, about 350 feet east of the barn north of the road, at a concrete culvert, in the top of the east end of the south head wall, 18 feet south of the centerline of the road, and about 1.5 feet lower than the road.                                                                  |
| RM 3              | 278.274                                 | V148 (United States Coast and Geodetic Survey), a standard disk, stamped "V 148 1942," located in the Town of Sodus, Wayne County, along Lake Road approximately 250 feet east of the Lake Road-North Centenary Road intersection, about 225 feet east of a schoolhouse, at a large concrete culvert, in the top of the west end of the north head wall, 16 feet north of the centerline of the road, and about level with the road.                                                                                                        |
| RM 4              | 264.0                                   | V768B on Munson Road, Town of Sodus, Wayne County, approximately 4,700 feet north of Munson Road-Lake Road intersection, established by Study Contractor in 1975. Point on the centerline of Munson Road in the pavement opposite drive on the west side of the road.                                                                                                                                                                                                                                                                       |
| RM 5              | 331.079                                 | T148 (United States Coast and Geodetic Survey), a standard disk, stamped "T 148 1942," located in the Town of Sodus, Wayne County, along Lake Road approximately 50 feet east of the Lake Road-Dufloo Road intersection, at a concrete culvert, in the top of the west end of the north head wall, 18 feet north of the centerline of the road, and about 2 feet lower than the road.                                                                                                                                                       |
| RM 6              | 271.2                                   | V771B on Private Road (located 2,150 feet east of Maple Avenue), Town of Sodus, Wayne County, approximately 5,600 feet north of Private Road-Lake Road intersection, established by Study Contractor in 1975. Point on centerline of Private Road in the pavement at south point of grass island.                                                                                                                                                                                                                                           |
| RM 7              | 319.612                                 | S148 (United States Coast and Geodetic Survey), a standard disk, stamped "S 148 1942," located in the Town of Sodus, Wayne County, along Lake Road approximately 800 feet east of the Lake Road-Maple Avenue intersection, about 100 feet west of the southwest corner of a small cemetery, at a large concrete culvert, in the top of the west end of the north head wall, 16 feet north of the centerline of the road, and about level with the road.                                                                                     |
| RM 8              | 319.232                                 | R148 (United States Coast and Geodetic Survey), a standard disk, stamped "R 148 1942," located in the Town of Sodus, Wayne County, on Lake Road, approximately 1,060 feet east of Lake Road-Pulver Road intersection, at the east one of two concrete culverts about 150 feet apart, about 350 feet east of a large brick house, about 110 feet southeast of a small house north of the road, in the top of the east end of the south head wall of the culvert, 15 feet south of the centerline of the road, and about level with the road. |

<sup>1</sup>National Geodetic Vertical Datum of 1929.



KEY TO MAP

500-Year Flood Boundary 100-Year Flood Boundary

ZONE B

Zone Designations\* With Date of Identification e.g., 12/2/74 100-Year Flood Boundary ZONE B 500-Year Flood Boundary

----513-----Base Flood Elevation Line With Elevation In Feet\*\* Base Flood Elevation in Feet (EL 987)

Where Uniform Within Zone\*\* RM7× Elevation Reference Mark ● M1.5

\*\*Referenced to the National Geodetic Vertical Datum of 1929

\*EXPLANATION OF ZONE DESIGNATIONS

EXPLANATION A Areas of 100-year flood; base flood elevations and flood hazard factors not determined. A0 Areas of 100-year shallow flooding with depth from

velocity (feet per second) less than 15. A1 - A30 Areas of 100-year flood; base flood elevations and flood hazard factors determined.

1 to 3 feet; product of flood depth (feet) and

A99 Areas of 100-year flood to be protected by a flood protection system under construction; base flood elevations and flood hazard factors not determined. B Areas between limits of 100-year flood and 500-year

flood; or areas of 100-year shallow flooding with depth less than 1 foot. (Medium shading)

C Areas of minimal flooding. (No shading)

D Areas of undetermined, but possible, flood hazards. V Areas of 100-year coastal flood with velocity (wave action); base flood elevations and flood hazard

factors not determined. VO Areas of 100-year shallow flooding with velocity; depth from 1 to 3 feet; product of depth (feet)

and velocity (feet per second) more than 15. V1 - V30 Areas of 100-year coastal flood with velocity (wave action); base flood elevations and flood hazard factors determined.

NOTES TO USER

Certain areas not in the special flood hazard areas (zones A and V) may be protected by flood control structures. This map is for flood insurance purposes only; it does not neces-

sarily show all areas subject to flooding in the community or all planimetric features outside special flood hazard areas. For adjoining map panels, see separately printed Index To Map Panels.

> INITIAL IDENTIFICATION AUGUST 16, 1974

CONVERSION TO REGULAR PROGRAM FEBRUARY 1, 1978

Consult NFIA servicing company or local insurance agent or broker to determine if properties in this community are eligible for flood insurance.




APPROXIMATE SCALE 800 0


NATIONAL FLOOD INSURANCE PROGRAM FLOOD INSURANCE RATE MAP TOWN OF SODUS, NEW YORK WAYNE COUNTY COMMUNITY-PANEL NUMBER 360898 0001 B PAGE 1 OF 6

EFFECTIVE FEBRUARY 1, 1978


U.S. DEPARTMENT OF HOUSING AND URBAN DEVELOPMENT

FEDERAL INSURANCE ADMINISTRATION









SPECIAL FLOOD HAZARD AREA

ZONE A

ZONE C

----- 513----

(EL 987)

RM7×

● M1.5

Base Flood Elevation Line With Elevation In Feet\*\*

River Mile

Base Flood Elevation in Feet
Where Uniform Within Zone\*\*

Elevation Reference Mark

\*\*Referenced to the National Geodetic Vertical Datum of 1929

\*EXPLANATION OF ZONE DESIGNATIONS

EXPLANATION OF ZONE DESIGNATION

EXPLANATION

EXPLANATION

Areas of 100-year flood; base flood elevations and flood hazard factors not determined.

A0 Areas of 00-year shallow flooding where depths are between one (1) and three (3) feet; average depths of inundation are shown, but no flood hazard factors are determined.

AH Areas of 100-year shallow flooding where depths

AH Areas of 100-year shallow flooding where depths are between one fit and three (3) feet; base flood elevations are shown but no flood hazard factors are determined.

A1-A30 Areas of 100-year flood, base flood elevations and flood hazard factors determined.

A99 Areas of 100-year flood to be protected by flood protection system under construction; base flood elevations and flood hazard factors not determined.

B Areas between limits of the 100-year flood and 500-year flood; or certain areas subject to 100-year flood.

Areas between limits of the 100-year flood and 500-year flood; or certain areas subject to 100-year flooding with average depths less than one (1) foot or where the contributing drainage area is less than one square mile; or areas protected by levees from the base flood.

Areas of minimal flooding.

V Areas of undetermined, but possible, flood hazards

V Areas of 100-year coastal flood with velocity (wave action); base flood elevations and flood hazard factors not determined.

V1-V30 Areas of 100-year coastal flood with velocity (wave action); base flood elevations and flood hazard factors

determined.

all planimetric features outside special flood hazard areas.

Certain areas not in the special flood hazard areas (zones A and V) may be protected by flood control structures.

This map is for flood insurance purposes only; it does not necessarily show all areas subject to flooding in the community or

NOTES TO USER

INITIAL IDENTIFICATION DECEMBER 20,1974

FLOOD HAZARD BOUNDARY MAP REVISIONS: 11/14/75

FLOOD INSURANCE RATE MAP EFFECTIVE:

FLOOD INSURANCE RATE MAP REVISIONS:

Refer to the FLOOD INSURANCE RATE MAP EFFECTIVE date shown on this map to determine when actual rates apply to structures in the zones where elevations or depths have been

To determine if flood insurance is available in this community, contact your insurance agent, or call the National Flood Insurance Program, at (800) 638-6620, or (800) 424-8872.

APPROXIMATE SCALE IN FEET O 800

NATIONAL FLOOD INSURANCE PROGRAM

FIRM
FLOOD INSURANCE
RATE MAP

TOWN OF LYONS, NEW YORK


WAYNE COUNTY

PANEL 1 OF 3
(SEE MAP INDEX FOR PANELS PRINTED)

COMMUNITY-PANEL NUMBER: 361226 0001 B

EFFECTIVE DATE: SEPTEMBER 7, 1979

U.S. DEPARTMENT OF HOUSING AND URBAN DEVELOPMENT FEDERAL INSURANCE ADMINISTRATION



KEY TO MAP

ZONE C

ZONEA

ZONE C

----*513*-----

(EL 987)

 $RM7 \times$ 

●M1.5 \*\*Referenced to the National Geodetic Vertical Datum of 1929

## \*EXPLANATION OF ZONE DESIGNATIONS

A flood insurance map displays the zone designations for a community according to areas of designated flood hazards. The zone designations used by FEMA are:

**EXPLANATION** Areas of 100-year flood; base flood elevations and

flood hazard factors not determined. Areas of 100-year shallow flooding where depths are between one (1) and three (3) feet; average depths of inundation are shown, but no flood hazard factors

Areas of 100-year shallow flooding where depths are between one (1) and three (3) feet; base flood elevations are shown, but no flood hazard factors

Areas of 100-year flood; base flood elevations and

flood hazard factors determined. Areas of 100-year flood to be protected by flood

protection system under construction; base flood elevations and flood hazard factors not determined. Areas between limits of the 100-year flood and 500year flood; or certain areas subject to 100-year flooding with average depths less than one (1) foot or where the contributing drainage area is less than one square mile; or areas protected by levees from the base flood. (Medium shading)

Areas of minimal flooding. (No shading)

Areas of undetermined, but possible, flood hazards. Areas of 100-year coastal flood with velocity (wave action); base flood elevations and flood hazard factors not determined.

Areas of 100-year coastal flood with velocity (wave action); base flood elevations and flood hazard factors

NOTES TO USER

Certain areas not in the special flood hazard areas (zones A and V) may be protected by flood control structures.

sarily show all areas subject to flooding in the community or all planimetric features outside special flood hazard areas.

> INITIAL IDENTIFICATION: JUNE 28, 1974

FLOOD HAZARD BOUNDARY MAP REVISIONS: MAY 21, 1976

FLOOD INSURANCE RATE MAP EFFECTIVE: MARCH 9, 1984

FLOOD INSURANCE RATE MAP REVISIONS:

Refer to the FLOOD INSURANCE RATE MAP EFFECTIVE date shown on this map to determine when actuarial rates apply to structures in the zones where elevations or depths have been estab-

To determine if flood insurance is available in this community, contact your insurance agent, or call the National Flood Insurance



APPROXIMATE SCALE

FLOOD INSURANCE RATE MAP

TOWN OF ROSE, NEW YORK WAYNE COUNTY


ONLY PANEL PRINTED

COMMUNITY-PANEL NUMBER 360897 0001 B

> EFFECTIVE DATE: MARCH 9, 1984







#### KEY TO SYMBOLS

ZONEC

ZONE A

ZONE C

(513' MSL)

RM7X

• M 1.5

#### \*EXPLANATION OF ZONE DESIGNATIONS

Area of special flood hazards (SFH)

"TO DETERMINE IF FLOOD INSURANCE IS AVAILABLE IN THIS COMMUNITY, CONTACT YOUR INSURANCE AGENT, OR CALL THE NATIONAL FLOOD INSURANCE PROGRAM AT (800) 832 6620

#### INITIAL IDENTIFICATION NOVEMBER 29, 1974

#### FLOOD HAZARD BOUNDARY MAP REVISIONS: NONE

FLOOD INSURANCE RATE MAP EFFECTIVE: JULY 9, 1962 FLOOD INSURANCE RATE MAP REVISIONS:

#### FEDERAL EMERGENCY MANAGEMENT AGENCY


FLOOD HAZARD BOUNDARY MAP H - 01-11 FLOOD INSURANCE RATE MAP 1 - 01-11


### MAP INDEX


TOWN OF BUTLER, NY (WAYNE CO.)


COMMUNITY NO. 361445 A

<sup>\*</sup> NOT PRINTED (FLOOD DATA NOT AVAILABLE)














#### **KEY TO SYMBOLS**

ZONE DESIGNATIONS\*

ZONE C

ZONE A

ZONE C

Base Flood Elevation Line with elevation in feet

**~**513**~** 

Base Flood Elevation where uniform within zone

(EL 987)

Elevation Reference Mark

RM7<sub>X</sub>

River Mile

• M1.5

#### **\*EXPLANATION OF ZONE DESIGNATIONS**

A flood insurance map displays the zone designations for a community according to areas of designated flood hazards. The zone designations used by FEMA are:

Zone

Expla

- Areas of 100-year flood; base flood elevations and flood hazard factors not determined.
- AD Areas of 100-year shallow flooding: flood depth 1 to 3 feet; product of flood depth (feet) and velocity (feet per second) less than 15.
- Areas of 100-year shallow flooding where depths are between one (1) and three (3) feet; base flood elevations are shown, but no flood hazard factors are determined.
- A1-A30 Areas of 100-year flood; base flood elevations and flood hazard factors determined.
- Asse Areas of 100-year flood to be protected by a flood protection system under construction; base flood elevations and flood hazard factors not determined.
- 8 Area between limits of 100-year flood and 500-year flood, areas of 100-year shallow flooding where depths less than 1 feet.
- C Areas outside 500-year flood.
- D Areas of undetermined, but possible, flood hezerds.
- Areas of 100-year coastal flood with velocity (wave action); base flood elevations and flood hazard factors not determined.
- V1.V30 Areas of 100-year coastal flood with velocity (wave action); base flood elevations and flood hazard factor determined.

#### NOTES TO USER

Certain areas not in the special flood hazard areas (zones A and V) may be protected by flood control extractures.

This map is for flood insurance purposes only; it does not necessarily show all areas subject to flooding in the community or all planimetric features outside special flood hazard areas.

Refer to the FLOOD INSURANCE RATE MAP EFFECTIVE date shown on this map to determine when acturial rates apply to structures in the zones where elevations or depths have been established.

To determine if flood insurance is available in this community, contact your insurance agent, or call the National Flood Insurance Program, at (800) 638-6620.

INITIAL IDENTIFICATION: NOVEMBER 15, 1974

FLOOD HAZARD BOUNDARY MAP REVISIONS: JUNE 11, 1976

FLOOD INSURANCE RATE MAP EFFECTIVE: JULY 6, 1984


FLOOD INSURANCE RATE MAP REVISIONS:

federal emergency management agency


FIRM
FLOOD INSURANCE RATE MAP
MAPINDEX

VILLAGE OF WOLCOTT, NY (WAYNE CO.)

**COMMUNITY NUMBER 361509 B** 







#### **LEGEND**

UNDEVELOPED COASTAL BARRIERS†







†Coastal barrier areas are normally located within or adjacent to special flood hazard areas.

#### **KEY TO SYMBOLS**

ZONE C
ZONE A

ZONE C

Base Flood Elevation Lin

---- 513-----

(513' MSL)

Elevation Reference I

RM7×

River N

●M 1.5

#### **\*EXPLANATION OF ZONE DESIGNATIONS**

A flood insurance map displays the zone designations for a community according to areas fo designated flood hazards. The zone designations used by FIA are

Zone Symbol

Category

A Area of special flood hazards (SFH) and without

Area of special flood hazards (SFH) with base flood elevations Zones are assigned according to flood hazard factors and dates of SFH identifiers

flood hazard factors, and dates of SFH identificiation.

Area of special flood hazards that have shallow flood depths (less than two feet) and/or unpredictable flow paths. Base flood elevations are not

Area of special flood hazards, with velocity, that are inundated by tidal floods Zones are assigned according to flood hazard factors and dates of SFH

Area of moderate flood hazard

Area of undetermined, but possible flood hazar

"TO DETERMINE IF FLOOD INSURANCE IS AVAILABLE IN THIS COMMUNITY, CONTACT YOUR INSURANCE AGENT, OR CALL THE NATIONAL FLOOD INSURANCE PROGRAM AT (800) 832 8620 OR (800) 424-8872"

INITIAL IDENTIFICATION

JUNE 28, 1974

FLOOD HAZARD BOUNDARY MAP REVISIONS:

JULY 2, 1976

FLOOD INSURANCE RATE MAP EFFECTIVE:

JULY 23, 1982

FLOOD INSURANCE RATE MAP REVISIONS:

June 2, 1992 - to add undeveloped coastal barriers.

#### FEDERAL EMERGENCY MANAGEMENT AGENCY

FLOOD HAZARD BOUNDARY MAP H - 01-03 FLOOD INSURANCE RATE MAP I - 01-03

### **MAP INDEX**

TOWN OF WOLCOTT, NY (WAYNE CO.)

COMMUNITY NO. 360901 C

